

WAVE POWER RACING 5W-50

Fully Synthetic Passenger Car Motor Oil

Product Description:

WAVE POWER RACING 5W-50 is a fully synthetic motor oil of exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines working under heavy load- and temperature conditions.

WAVE POWER RACING 5W-50 has been especially developed to withstand high pressures and temperatures encountered under racing conditions.

WAVE POWER RACING 5W-50 provides outstanding thermal stability. Improved viscosity temperature characteristics and the exceptional low temperature fluidity reduce friction and give a higher power output.

WAVE POWER RACING 5W-50 reduces internal friction resulting in lower wear and fuel consumption. The optimised dispersant/detergent properties of the oil effectively prevents deposit formation on the internal engine parts, giving a longer life to the engine.

WAVE POWER RACING 5W-50 is recommended for gasoline-, diesel- and LPG fuelled engines of passenger cars and light trucks performing under extreme conditions.

Specifications:		
Exceeds: ACEA A3/B4, API SM/CF		
Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	5W-50
Density	ASTM D4052	850 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	109 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	18 mm ² /s
Viscosity CCS @ -30°C	ASTM D5293	<6600 mm ² /s
Viscosity Index	ASTM D2270	175
Flash Point	ASTM D92	>200°C
Pour Point	ASTM D97	-45°C
Total Base Number (TBN)	ASTM D2896	11.5 mgKOH/g
Sulphated Ash	ASTM D874	1.3% wt