

WAVE POWER SM 5W-40

Fully Synthetic Passenger Car Motor Oil

Product Description:

WAVE POWER SM 5W-40 is a supreme performance passenger car motor oil formulated from the latest additive technology in fully synthetic base stocks. WAVE POWER SM 5W-40 has been especially developed for all gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles. WAVE POWER SM 5W-40 has been designed to exceed the latest Original Equipment Manufacturers' (OEM's) service fill specifications and exceeds the requirements of most modern European-, North American and Japanese car manufacturers.

WAVE POWER SM 5W-40 has outstanding thermo-oxidative stability, effectively preventing the formation of sludge and deposits, resulting in a prolonged engine life. WAVE POWER SM 5W-40 gives improved fuel economy and allows extended oil drain intervals, reducing the costs of ownership. Excellent low temperature fluidity facilitates cold starting of the engine and effectively provides wear protection at low temperatures.

WAVE POWER SM 5W-40 is recommended for all modern vehicles, including high performance, turbo-charged, multi valve, direct injected gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

Specifications:

Exceeds: ACEA A3/B4, API SM/CF, MB 229.3, VW 502.00/505.00

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	5W-40
Density @ 15°C	ASTM D4052	857 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	85 mm ² /s
Kinematic Viscosity @ 40°C	ASTM D7042	14.4 mm ² /s
CCS Viscosity @ -25°C	ASTM D5293	<6600 cP
Viscosity Index	ASTM D2270	155
Flash Point	ASTM D92	230°C
Pour Point	ASTM D97	-42°C
Total Base Number (TBN)	ASTM D2896	9.6 mgKOH/g
Sulfated Ash	ASTM D874	1.16 wt %