

## WAVE POWER SL 10W-40

### Semi Synthetic Passenger Car Motor Oil

#### Product Description:

WAVE POWER SL 10W-40 is a high performance semi-synthetic passenger car motor oil formulated from the latest additive technology and carefully selected synthetic- and mineral base stocks.

WAVE POWER SL 10W-40 has been especially developed for all gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

WAVE POWER SL 10W-40 has been designed to exceed the requirements of the Original Equipment Manufacturers' (OEM's) service fill specifications.

WAVE POWER SL 10W-40 has very good thermo-oxidative stability, effectively preventing the formation of sludge and deposits, resulting in a prolonged engine life.

WAVE POWER SL 10W-40 gives improved fuel economy and allows extended oil drain intervals, reducing the costs of ownership. Excellent low temperature fluidity facilitates cold starting of the engine and effectively provides wear protection at low temperatures.

WAVE POWER SL 10W-40 is recommended for all modern vehicles, including high performance, turbo-charged, multi valve, direct injected gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

WAVE POWER SL 10W-40 exceeds the requirements of most modern European, North American and Japanese car manufacturers.

<b>Specifications:</b>		
Exceeds: ACEA A3/B4, API SL/CF, MB 229.1, VW 505.00		
<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
SAE Viscosity Grade	SAE J300	10W-40
Kinematic Viscosity @ 40°C	ASTM D7042	97 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	14.3 mm <sup>2</sup> /s
Cranking Viscosity @ -25°C	ASTM D5293	<7000 mPa.s
Viscosity Index	ASTM D2270	145
Density @ 15°C	ASTM D4052	873 kg/m <sup>3</sup>
Flash Point (COC)	ASTM D92	205°C
Pour Point	ASTM D97	-33°C
Total Base Number	ASTM D2896	8.1 mg KOH/g
Sulphated Ash	ASTM D874	0.95 wt%