

WAVE POWER SL 20W-50

Mineral Passenger Car Motor Oil

Product Description:

WAVE POWER SL 20W-50 is a high performance mineral passenger car motor oil formulated from the latest additive technology and carefully selected mineral base stocks.

WAVE POWER SL 20W-50 has been especially developed for all gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

WAVE POWER SL 20W-50 has been designed to exceed the requirements of the Original Equipment Manufacturers' (OEM's) service fill specifications.

WAVE POWER SL 20W-50 has very good thermo-oxidative stability, effectively preventing the formation of sludge and deposits, resulting in a prolonged engine life.

WAVE POWER SL 20W-50 is recommended for all modern vehicles, including high performance, turbo-charged, multi valve, direct injected gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

WAVE POWER SL 20W-50 exceeds the requirements of most modern European, North American and Japanese car manufacturers.

Specifications:		
Exceeds: ACEA A3/B3, API SL/CF, MB 229.1, VW 505.00		
Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	20W-50
Kinematic Viscosity @ 40°C	ASTM D7042	150 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	17.0 mm ² /s
Cranking Viscosity @ -15°C	ASTM D5293	<9500 mPa.s
Viscosity Index	ASTM D2270	120
Density @ 15°C	ASTM D4052	891 kg/m ³
Flash Point (COC)	ASTM D92	215°C
Pour Point	ASTM D97	-21°C
Total Base Number	ASTM D2896	8.9 mg KOH/g
Sulphated Ash	ASTM D874	1.2 wt%