

WAVE POWER SF 15W-40

Mineral Passenger Car Motor Oil

Product Description:

WAVE POWER SF 15W-40 is a mineral passenger car motor oil formulated from carefully selected additives and mineral base stocks.

WAVE POWER SF 15W-40 has been developed for older gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

WAVE POWER SF 15W-40 has good thermo-oxidative stability, effectively preventing the formation of sludge and deposits. Effective rust inhibitors prevent corrosion of critical engine parts. The use of advanced anti-wear additives results in prolonged engine life. Good 'stay in grade' properties of the oil ensures reliable lubrication even at higher load- and temperature conditions.

WAVE POWER 15W-40 is recommended for older vehicles, including turbo-charged gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

Specifications:		
Exceeds: API SF/CD		
Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	15W-40
Kinematic Viscosity @ 40°C	ASTM D7042	104 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	14.1 mm ² /s
Cranking Viscosity @ -20°C	ASTM D5293	6550 mPa.s
Viscosity Index	ASTM D2270	125
Density @ 15°C	ASTM D4052	883 kg/m ³
Flash Point (COC)	ASTM D92	220°C
Pour Point	ASTM D97	-27°C
Total Base Number	ASTM D2896	4.9 mg KOH/g
Sulphated Ash	ASTM D874	0.66 wt%