

## WAVE POWER SF 20W-50

### Mineral Passenger Car Motor Oil

#### Product Description:

WAVE POWER SF 20W-50 is a mineral passenger car motor oil formulated from carefully selected additives and mineral base stocks.

WAVE POWER SF 20W-50 has been developed for older gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

WAVE POWER SF 20W-50 has good thermo-oxidative stability, effectively preventing the formation of sludge and deposits. Effective rust inhibitors prevent corrosion of critical engine parts. The use of advanced anti-wear additives results in prolonged engine life.

Good stay in grade properties of the oil ensure reliable lubrication even at higher load- and temperature conditions.

WAVE POWER SF 20W-50 is recommended for older vehicles, including turbo-charged gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

<b>Specifications:</b>		
Exceeds: API SF/CD		
<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
SAE Viscosity Grade	SAE J300	20W-50
Kinematic Viscosity @ 40°C	ASTM D7042	150 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	17.0 mm <sup>2</sup> /s
Cranking Viscosity @ -15°C	ASTM D5293	<9500 mPa.s
Viscosity Index	ASTM D2270	120
Density @ 15°C	ASTM D4052	891 kg/m <sup>3</sup>
Flash Point (COC)	ASTM D92	215°C
Pour Point	ASTM D97	-21°C
Total Base Number	ASTM D2896	4.9 mg KOH/g
Sulphated Ash	ASTM D874	0.66 wt%