

WAVE POWER SL 0W-30

Fully Synthetic Passenger Car Motor Oil

Product Description:

WAVE POWER SL 0W-30 is a high performance fully synthetic passenger car motor oil formulated high quality base stocks and modern additive technology.

WAVE POWER SL 0W-30 has been specially developed for all modern turbocharged, high output gasoline and diesel engines of passenger cars, SUVs, light vans and trucks.

WAVE POWER SL 0W-30 has outstanding thermo-oxidative stability, effectively preventing the formation of sludge and deposits resulting in a prolonged engine life. Excellent low temperature fluidity facilitates cold starting of the engine and effectively provides wear protection at low temperatures. Superior antiwear technology prolongs engine life.

WAVE POWER SL 0W-30 is recommended for all modern vehicles including high performance, turbo-charged, multi valve, direct injection gasoline and diesel engines of passenger cars.

WAVE POWER SL 0W-30 is specially recommended for all Audi cars including TT (163 KW), S3 & RS4 models for long life service and improved fuel economy.

Specifications:		
Exceeds: ACEA A3/B4, API SJ/CF, VW 502.00/505.00/503.01, MB 229.3, BMW Longlife-98		
Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	0W-30
Kinematic Viscosity @ 40°C	ASTM D7042	64 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	11.2 mm ² /s
Cranking Viscosity @ -35°C	ASTM D5293	<6000 mPa.s
Viscosity Index	ASTM D2270	165
Density @ 15°C	ASTM D4052	850 kg/m ³
Flash Point (COC)	ASTM D92	200°C
Pour Point	ASTM D97	-36°C
Total Base Number	ASTM D2896	11.5 mg KOH/g
Sulphated Ash	ASTM D874	1.5 wt%