

WAVE POWER C2 5W-30

Fully Synthetic "Mid SAPS" Passenger Car Motor Oil

Product Description:

WAVE POWER C2 5W-30 is an advanced Mid SAPS fuel economy passenger car motor oil formulated from specially selected additive technology in fully synthetic base stocks and has been especially developed to exceed the service fill requirements of API C2 specification.

WAVE POWER C2 5W-30 has outstanding thermo-oxidative stability effectively preventing the formation of sludge and deposits, resulting in a prolonged engine life and gives improved fuel economy and allows extended oil drain intervals, reducing the costs of ownership. Excellent low temperature fluidity facilitates cold starting of the engine and effectively provides wear protection at low temperatures.

WAVE POWER C2 5W-30 is a so called low High Temperature High Shear (HTHS) oil. Reduced deposit- and sludge formation in engine and turbo-charger ensures rated power and torque. The excellent anti wear technology ensures the best possible protection regarding engine durability.

WAVE POWER C2 5W-30 is strongly recommended for the latest generation high performance gasoline-, LPG- and diesel fuelled engines in passenger cars and light commercial vehicles requiring ACEA A1/B1, A5/B5, ACEA C2 oils.

Specifications:

Exceeds: ACEA A1/B1, A5/B5, ACEA C2, API SM/CF, Renault 0700, PSA B 71 2290.

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	5W-30
Density @ 15°C	ASTM D4052	856 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	86 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	11.7 mm ² /s
CCS Viscosity @ -30°C	ASTM D5293	<6600 cP
Viscosity Index	ASTM D2270	152
Flash Point	ASTM D92	230°C
Pour Point	ASTM D97	-36°C
Total Base Number (TBN)	ASTM D2896	7.5 mgKOH/g
Sulfated Ash	ASTM D874	<0.8 wt %