

TIDAL MONO POWER CF 20W-20

Mineral Heavy Duty Diesel Engine Oil

Product Description:

TIDAL MONO POWER OIL CF 20W-20 is a heavy duty engine oil developed to meet the requirements of a variety of engines operating under severe conditions.

TIDAL MONO POWER OIL CF 20W-20 is formulated from highly refined base stocks and balanced additives to provide effective protection to engines operating under various environments.

TIDAL MONO POWER OIL CF 20W-20 is suitable for use in a wide range of on and off-highway applications where such type of lubricant is recommended.

TIDAL MONO POWER OIL CF 20W-20 has improved detergency that helps to reduce deposits and keeps engines cleaner, better thermo-oxidative stability protects against sludge build-up, deposits & oil degradation and controls oil thickening. Effective anti-wear properties protects engine components against wear to offer extended engine life and reduced maintenance costs and good corrosion inhibition properties protects against corrosion and wear.

TIDAL MONO POWER OIL CF 20W-20 is suitable for turbocharged and naturally aspirated engines of most engine manufacturers working under the most demanding conditions.

| Specifications: | | |
|-----------------------------|---------------------|------------------------|
| Exceeds: API CF/SF | | |
| Property: | Test Method: | Typical Values: |
| SAE Viscosity Grade | SAE J300 | 20W-20 |
| Kinematic Viscosity @ 40°C | ASTM D7042 | 68 mm ² /s |
| Kinematic Viscosity @ 100°C | ASTM D7042 | 8.6 mm ² /s |
| Cranking Viscosity @ -15°C | ASTM D5293 | <9500 mPa.s |
| Viscosity Index | ASTM D2270 | 100 |
| Density @ 15°C | ASTM D4052 | 884 kg/m ³ |
| Flash Point (COC) | ASTM D92 | 220°C |
| Pour Point | ASTM D97 | -27°C |
| Total Base Number | ASTM D2896 | 10.6 mg KOH/g |
| Sulphated Ash | ASTM D874 | 1.4 wt% |