

## **TIDAL MONO POWER CF 30**

## **Mineral Heavy Duty Diesel Engine Oil**

## **Product Description:**

TIDAL POWER CF 30 is a heavy duty engine oil developed to meet the requirements of a variety of engines operating under severe conditions.

TIDAL POWER CF 30 is formulated from highly refined base stocks and balanced additives to provide effective protection to engines operating under various environments.

TIDAL POWER CF 30 is suitable for use in a wide range of on and off-highway applications where such type of lubricant is recommended.

TIDAL POWER CF 30 has improved detergency that helps to reduce deposits and keeps engines cleaner, better thermo-oxidative stability protects against sludge build-up, deposits & oil degradation and controls oil thickening. Effective antiwear properties protects engine components against wear to offer extended engine life and reduced maintenance costs and good corrosion inhibition properties protects against corrosion and wear.

TIDAL POWER CF 30 is suitable for turbocharged and naturally aspirated engines of most engine manufacturers working under the most demanding conditions.

Specifications

Specifications: Exceeds: API CF/SF			
Property:	Test Method:	Typical Values:	
SAE Viscosity Grade	SAE J300	30	
Kinematic Viscosity @ 40°C	ASTM D7042	99 mm <sup>2</sup> /s	
Kinematic Viscosity @ 100°C	ASTM D7042	11.3 mm <sup>2</sup> /s	
Viscosity Index	ASTM D2270	98	
Density @ 15°C	ASTM D4052	892 kg/m³	
Flash Point (COC)	ASTM D92	220°C	
Pour Point	ASTM D97	-18°C	
Total Base Number	ASTM D2896	10.6 mg KOH/g	
Sulphated Ash	ASTM D874	1.4 wt%	