

STREAM POWER SYN 2T

Fully Synthetic 2-stroke Motorcycle Oil

Product Description:

STREAM POWER SYN 2T is a fully synthetic lubricant developed for air & water cooled 2-stroke gasoline engines. STREAM POWER SYN 2T's special formulation ensures excellent engine protection, cleanliness and low smoke even under extreme operating conditions.

STREAM POWER SYN 2T offers very good lubricity against piston scuffing and wear of engine components. The advanced formulation provides exceptional control against engine deposits, exhaust system blocking and extended engine life without power loss, and reduces visible exhaust smoke. Low ash additive technology prevents pre-ignition and spark plug and easy miscibility with gasoline ensure stable homogeneous mixture even at low ambient temperatures.

STREAM POWER SYN 2T is recommended for high-powered 2-stroke motorcycles/scooters operating under different conditions.

STREAM POWER SYN 2T is suitable for oil-injection and premix lubrication systems; always follow manufacturer's recommendations for oil-fuel ratio.

STREAM POWER SYN 2T is also suitable for 2-stroke engines in all terrain vehicles, snow mobiles, lawn mowers and other applications requiring oils of this quality.

| Specifications: | | |
|------------------------------------|---------------------|------------------------|
| Exceeds: API TC, ISO-LEGD, JASO FD | | |
| Property: | Test Method: | Typical Values: |
| Kinematic Viscosity @ 40°C | ASTM D7042 | 68 mm ² /s |
| Kinematic Viscosity @ 100°C | ASTM D7042 | 11 mm ² /s |
| Viscosity Index | ASTM D2270 | 150 |
| Density @ 15°C | ASTM D4052 | 878 kg/m ³ |
| Flash Point (COC) | ASTM D92 | 90°C |
| Pour Point | ASTM D97 | -45°C |
| Total Base Number | ASTM D2896 | 1.6 mg KOH/g |
| Sulphated Ash | ASTM D874 | 0.13 wt% |