

## AUTOGEAR POWER EP 85W-140

### Automotive Gear Oil

#### Product Description:

AUTOGEAR POWER EP 85W-140 is a high performance gear lubricant designed to provide effective lubrication in a wide range of automotive transmissions and axle drives where an API GL-4 oil is specified.

AUTOGEAR POWER EP 85W-140 is formulated from carefully selected base stocks and well balanced extreme pressure additives. AUTOGEAR POWER EP 85W-140 gives excellent protection towards gear components regarding wear and scoring. Furthermore the oil provides very good anti-corrosion and has been carefully inhibited against the formation of foam.

AUTOGEAR POWER EP 85W-140 exceeds the specifications of API GL-4 and US MIL-L-2105, as well as the requirements of most "Original Equipment Manufacturers"(OEMs).

AUTOGEAR POWER EP 85W-140 is recommended for manual transmissions and transaxles requiring oils meeting API GL-4 and for on-road passenger cars, light and heavy duty trucks, buses and vans. AUTOGEAR POWER EP 85W-140 is also recommended for off-highway equipment in construction, mining and agriculture.

<b>Specifications:</b>		
Exceeds: API GL-4, US Army MIL-L-2105		
<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
SAE Viscosity Grade	SAE J300	85W-140
Kinematic Viscosity @ 40°C	ASTM D7042	410 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	29.1 mm <sup>2</sup> /s
Brookfield Viscosity @ -12°C	ASTM D2983	<150000 cP
Viscosity Index	ASTM D2270	96
Density @ 15°C	ASTM D4052	909 kg/m <sup>3</sup>
Flash Point (COC)	ASTM D92	>200°C
Pour Point	ASTM D97	-15°C