

AUTOGEAR POWER MP 80W-90

Automotive Gear Oil

Product Description:

AUTOGEAR POWER MP 80W-90 is a high performance gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives where an API GL-5 oil is specified.

AUTOGEAR POWER MP 80W-90 is formulated from carefully selected base stocks and well balanced extreme pressure additives. AUTO GEAR POWER MP 80W-90 gives excellent protection towards gear components regarding wear and scoring. Furthermore AUTO GEAR POWER MP 80W-90 provides very good anti-corrosion protection and has been carefully inhibited against the formation of foam.

AUTOGEAR POWER MP 80W-90 exceeds the specifications of API GL-5 and MIL-L-2105D, as well as the requirements of most "Original Equipment Manufacturers" (OEMs).

AUTO GEAR POWER MP 80W-90 is recommended for certain manual transmissions and final drives requiring oils meeting API GL-5 in on road passenger cars, light- and heavy duty trucks, buses and vans. AUTO GEAR POWER MP 80W-90 is also recommended for off highway equipment, in construction, mining and agriculture.

Specifications:		
Exceeds: API GL-5, US Army MIL-L-2105D		
Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	80W-90
Kinematic Viscosity @ 40°C	ASTM D7042	162 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	14.4 mm ² /s
Brookfield Viscosity @ -26°C	ASTM D2983	<150000 cP
Viscosity Index	ASTM D2270	96
Density @ 15°C	ASTM D4052	902 kg/m ³
Flash Point (COC)	ASTM D92	>190°C
Pour Point	ASTM D97	-27°C