

AUTOGEAR POWER MP 85W-90

Automotive Gear Oil

Product Description:

AUTOGEAR POWER MP 85W-90 is a high performance gear lubricant designed to provide excellent lubrication in a wide range of heavy duty automotive transmissions, axles and final drives where an API GL-5 oil is specified.

AUTOGEAR POWER MP 85W-90 is formulated from carefully selected base stocks and well balanced extreme pressure additives. AUTOGEAR POWER MP 85W-90 gives excellent protection towards gear components regarding wear and scoring. Furthermore AUTOGEAR POWER MP 85W-90 provides very good anti-corrosion protection and has been carefully inhibited against the formation of foam.

AUTOGEAR POWER MP 85W-90 exceeds the specifications of API GL-5 and MIL-L-2105D, as well as the requirements of most "Original Equipment Manufacturers" (OEMs).

AUTOGEAR POWER MP 85W-90 is suitable for heavy duty non-synchronized manual transmissions, axles and final drives requiring oils meeting API GL-5 in on road passenger cars, light- and heavy duty trucks, buses and vans and is also recommended for off highway equipment, in construction, mining and agriculture.

Specifications:		
Exceeds: API GL-5, US Army MIL-L-2105D, MB 235.6, ZF TE-ML 05A/16C/17B/19B/21A		
Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J306	85W-90
Density @ 15°C	ASTM D4052	905 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	155 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	17.2 mm ²
Cranking Viscosity @ -12°C	ASTM D5293	<150000 cP
Viscosity Index	ASTM D2270	95
Flash Point (COC)	ASTM D92	205°C
Pour Point	ASTM D97	-21°C