

ATF POWER DX III

Automatic Transmission Fluid

Product Description:

ATF POWER DX III is a fluid for automatic transmissions in vehicles specifying the use of DEXRON® III quality fluids. High quality base oils and special additives ensure improved resistance to oxidation, possesses better low temperature fluidity and shows improved frictional properties.

ATF POWER DX III exceeds the performance requirements of General Motors DEX-RON® III specification and provides excellent shifting behaviour under all conditions.

ATF POWER DX III has excellent thermo-oxidative stability preventing the formation of undesirable deposits.

ATF POWER DX III is recommended for all vehicles of General Motors requiring DEXRON®-IIIG quality fluids as well as in vehicles of Ford requiring so called MER-CON® fluids.

Specifications: Exceeds: General Motors DEXRON®IIIG, Ford MERCON®		
Property:	Test Method:	Typical Values:
Kinematic Viscosity @ 40°C	ASTM D7042	41.6 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	7.8 mm ² /s
Brookfield Viscosity @ -40°C	ASTM D2983	<20000 cP
Viscosity Index	ASTM D2270	165
Density @ 15°C	ASTM D4052	852 kg/m³
Flash Point (COC)	ASTM D92	>190°C
Pour Point	ASTM D97	-39°C