

ATF POWER DX VI

Automatic Transmission Fluid

Product Description:

ATF POWER DX VI is a supreme performance long lasting automatic transmission fluid, especially developed for all 2006, and beyond, General Motors vehicles equipped with automatic transmissions.

ATF POWER DX VI is formulated with exceptional quality base fluids and the latest additive technology in order to achieve outstanding oxidation resistance, improved friction characteristics and optimal wear protection.

ATF POWER DX VI has outstanding thermo-oxidative stability, preventing the formation of undesirable deposits. The high viscosity index ensures adequate lubrication in both high operating and low starting temperatures. Enhanced low temperature fluidity assists in good cold shifting performance.

ATF POWER DX VI provides better protection against rust and corrosion while the excellent foam control leads to long lasting, smooth shifting behaviour.

ATF POWER DX VI is recommended for all vehicles of General Motors from 2006 and beyond equipped with Hydramatic transmissions. General Motors vehicles with six speed Hydramatic transmissions requiring DEXRON® VI quality fluids. Being fully backwards compatible, ATF POWER DX VI is also recommended for automatic automatic transmissions requiring DEXRON® III (H), DEXRON® III(G), DEXRON®IIE and DEXRON®IID fluids.

Specifications:		
Exceeds: General Motors DEXRON®VI		
Property:	Test Method:	Typical Values:
Kinematic Viscosity @ 40°C	ASTM D7042	29.9 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	6.1 mm ² /s
Brookfield Viscosity @ -40°C	ASTM D2983	<15000 cP
Viscosity Index	ASTM D2270	150
Density @ 15°C	ASTM D4052	842 kg/m ³
Flash Point (COC)	ASTM D92	>190°C
Pour Point	ASTM D97	-48°C