

## CVT POWER FLUID

### Automatic Transmission Oil

#### Product Description:

CVT POWER FLUID is an ultra high performance transmission oil formulated with selected base stocks and specially recommended for use in the latest generations of Continuously Variable Transmission (CVT) - gearboxes which transfer traction via steel-made traction chains or push-belts.

CVT POWER FLUID offers outstanding antiwear protection even under severe operating conditions and meets the most demanding requirements of a CVT transmission and offers excellent low temperature properties and ensures very stable friction coefficients over the entire service time for reliable power transmission and lowest friction losses. The special additive package ensures best ageing and oxidation stability as well as outstanding protection against foaming which is specially required in CVT transmissions.

CVT POWER FLUID has been tested successfully to be used in many CVT's of various brands such as Audi Multitronic & Mercedes Benz Autotronic. The drain intervals of the Original Equipment Manufacturers (OEMs) are mandatory.

#### Specifications:

Exceeds: MB 236.20, Ford WSS-M2C928-A, BMW 83 22 0 136 376 / BMW 83 22 0 429 154, VW TL 521 80 (G 052 180)

Property:	Test Method:	Typical Values:
Kinematic Viscosity @ 40°C	ASTM D7042	34 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	7.0 mm <sup>2</sup> /s
Brookfield Viscosity @ -40°C	ASTM D2983	11900 cP
Viscosity Index	ASTM D2270	173
Density @ 15°C	ASTM D4052	848 kg/m <sup>3</sup>
Flash Point (COC)	ASTM D92	210°C
Pour Point	ASTM D97	-51°C
Foaming Tendency Seq.I/II	ASTM D892	30/0 // 30/0