

SUPER TRACTOR POWER 10W-30

Super Tractor Oil Universal (STOU)

Product Description:

SUPER TRACTOR POWER 10W-30 is a high quality so called "Super Tractor Oil Universal"(STOU) lubricant formulated with carefully selected mineral base stocks and modern additives

SUPER TRACTOR POWER 10W-30 has been developed for use in tractors, combines harvesters and off road machinery with naturally aspirated or turbo charged diesel engines. Furthermore the product has been designed to serve in the hydraulic system, lubricate the transmission and power take off, final drive and oil immersed "wet brakes".

SUPER TRACTOR POWER 10W-30 possesses viscometric characteristics allowing excellent cold starting in winter time and optimal response of the hydraulics under all conditions.

SUPER TRACTOR POWER 10W-30 ensures optimal protection of the engine, effectively preventing wear and sludge; apart of that the product shows superior performance in transmissions of off road equipment.

Specifications:

Exceeds: API CF-4/CF/SF, API GL-4, John Deere J27C, MF 1139/1144, Ford M2C-159B
Allison C-4, Caterpillar TO-2, ZF TE-ML 06B/07B

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	10W-30
Kinematic Viscosity @ 40°C	ASTM D7042	68 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	11.0 mm ² /s
Cranking Viscosity @ -25°C	ASTM D5293	<7000 mPa.s
Viscosity Index	ASTM D2270	130
Density @ 15°C	ASTM D4052	879 kg/m ³
Flash Point (COC)	ASTM D92	205°C
Pour Point	ASTM D97	-30°C
Total Base Number	ASTM D2896	10.6 mg KOH/g
Sulphated Ash	ASTM D874	1.4 wt%