

UNIVERSAL TRACTOR POWER 85W

Universal Tractor & Transmission Oil (UTTO)

Product Description:

UNIVERSAL TRACTOR POWER 85W is a high quality so called "Universal Tractor Transmission Oil" (UTTO) lubricant formulated with carefully selected mineral base stocks and modern additives.

UNIVERSAL TRACTOR POWER 85W is suitable for modern high performance tractors, requiring one single lubricant for the hydraulic system, transmission, differential, power take off and oil immersed "wet" brakes.

UNIVERSAL TRACTOR POWER 85W is formulated with a shear stable viscosity index improver providing excellent fluidity at low temperatures.

UNIVERSAL TRACTOR POWER 85W contains very sophisticated anti wear and extreme pressure (EP) additives to prevent scuffing and scoring of metal surfaces under high speed, shock load conditions.

UNIVERSAL TRACTOR POWER 85W withstands long-lasting high loads and ensures the proper functioning of the hydraulic system

Note; this product should not be used for engine lubrication!!

Specifications: Exceeds: API GL-4, John Deere J20C, Ford M2C 134D, MF CMS M1135/1143/1145 Case NH MAT 3525&3526 , ZF TE ML 03E/05E		
Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	85W
Kinematic Viscosity @ 40°C	ASTM D7042	66 mm²/s
Kinematic Viscosity @ 100°C	ASTM D7042	11.2 mm ² /s
Brookfield Viscosity @ -18°C	ASTM D2983	<4000 mPa.s
Viscosity Index	ASTM D2270	138
Density @ 15°C	ASTM D4052	886 kg/m³
Flash Point (COC)	ASTM D92	210°C
Pour Point	ASTM D97	-30°C
Total Base Number	ASTM D2896	9.4 mg KOH/g
Sulphated Ash	ASTM D874	1.3 wt%