

AUTOGEAR POWER TX 75W-80

Full Synthetic Universal Transmission Oil

AUTOGEAR POWER TX 75W-80 is an universal high performance transmission oil based on synthetic technology used in heavy loaded manual shifted transmission of passenger cars, light vans and medium/heavy loaded commercial vehicles where a SAE 75W-80, GL-4 is prescribed.

AUTOGEAR POWER TX 75W-80 is based on special selected high performance synthetic base oil in combination with an unique EP-additive package to for fill the following properties.

- Excellent EP-properties.
- Excellent shifting even at low temperatures.
- Low pour point, -42°C
- Fuel saving properties.
- Excellent protection against foam, corrosion and wear.
- Unique thermal- and oxidation stability.
- Suited for extended drain intervals.

Specifications:			
Exceeds: API GL-4, MIL-L-2105, ZF TE-ML 02L, MAN 341 Z4/E3, Volvo 97305, Eaton, Iveco, Renault			
Properties:	Test Method:	Unit	Typical Value:
SAE Grade	SAE J300		75W-80
Density @15°C	ASTM D4052	kg/m ³	858
Kin. Viscosity @40°C	ASTM D7042	mm ² /s	54.5
Kin. Viscosity @100°C	ASTM D7042	mm ² /s	9.4
Viscosityindex	ASTM D2270		156
Flash point COC	ASTM D92	°C	>201
Pour Point	ASTM D97	°C	-42