

AUTOGEAR POWER SYN 75W-85

Synthetic Oil For Universal Drive Line

AUTOGEAR POWER SYN 75W-85 is an universal high performance transmission on synthetic technology for use in manual shifted transmission of the modern passenger car and light vans where an API GL-5, SAE 75W-85 is prescribed.

AUTOGEAR POWER SYN 75W-85 is based on special selected high performance synthetic base oil in combination with a special selected EP-additive package to reach to following properties:

- Excellent EP-properties.
- Good shifting even at low temperatures.
- Low Pour Point.
- Fuel saving properties.
- Excellent protection against the forming of foam, corrosion and wear.
- High thermal- and oxidation stability.
- Long drain intervals.
- Suitable for so called limited slip differentials.

Specifications:

Exceeds: API GL-5, MB 235.7, ZF TE-ML 18, VW G 052 145, VW G 052 190, VW G 055 190, Alfa Romeo, BMW, Fiat, Lancia

Properties:	Test Method:	Unit	Typical Value:
SAE Grade	SAE J300		75W-85
Density @15°C	DIN 51757	kg/m ³	870
Kin. Viscosity @40°C	DIN 51562-1	mm ² /s	81.5
Kin. Viscosity @100°C	DIN 51562-1	mm ² /s	12.1
Viscosityindex	DIN ISO 2909		144
Viscosity Brookfield -40°C, max	DIN 51398	mPas	55000
Flash point COC	ASTM D92	°C	>201
Pour point	ASTM D97	°C	-51