

## **SLIDEWAY POWER 220**

**Slideway Oil** 

## **Product Description:**

SLIDEWAY POWER 220 is specially formulated for the lubrication of slide ways on machine tools.

SLIDEWAY POWER 220 is formulated with special additives to impart tackiness and adhesiveness.

SLIDEWAY POWER 220 overcomes stick-slip motion associated with slow moving parts.

SLIDEWAY POWER 220 can be used on all horizontal and vertical slide ways where a good quality lubricant is required for protection of the slide ways.

SLIDEWAY POWER 220 has good demulsifying properties and protects slide ways against staining and corrosion.

<b>Specifications:</b> Exceeds: ISO 6743-4 HG, ISO 6743-13 GA, Cincinnati Milacron P-50		
Property:	Test Method:	Typical Values:
ISO Viscosity Grade	-	220
Kinematic Viscosity @ 100°C	ASTM D7042	18.7 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	95
Density @ 15°C	ASTM D4052	898 kg/m³
Flash Point (COC)	ASTM D92	>240°C
Pour Point	ASTM D97	-18°C
Neutralisation No.	ASTM D974	0.4
CM Stick-Slip Frictional Test,	СМ	<0.8
Ratio of static to kinetic friction		
Copper Corrosion, 3hrs @ 100°C	ASTM D130	1b max.