

COMPRESSOR POWER 68

Air Compressor Oil

Product Description:

COMPRESSOR POWER 68 is a premium quality, mineral based compressor oils for use in reciprocating compressors and some rotary air compressors.

COMPRESSOR POWER 68 is formulated with carefully selected base stocks fortified with additives to ensure very high resistance towards oxidation.

COMPRESSOR POWER 68 shows very low carbon deposit forming tendencies reducing the risk of fire or explosion.

COMPRESSOR POWER 68 is recommended for the cylinder and crankcase lubrication of air or inert gas compressors operating with high discharge temperatures.

COMPRESSOR POWER 68 effectively protects against rust and oxidation.

Specifications:		
Exceeds: DIN 51506: VBL/VCL/VDL, ISO 6743-3A: L-DAA/DAB/DAG/DAH		
Property:	Test Method:	Typical Values:
ISO Viscosity Grade	-	68
Kinematic Viscosity @ 100°C	ASTM D7042	8.5 mm ² /s
Viscosity Index	ASTM D2270	103
Density @ 15°C	ASTM D4052	885 kg/m ³
Flash Point (COC)	ASTM D92	>230°C
Pour Point	ASTM D97	-21°C
Load-carrying property FZG A/8,3/90°C Fail stage, minimum	DIN 51354-2	12
Demulsibility @ 54°C	DIN 51599	<30 min.